POWERTIP TECH. CORP.

SPECIFICATIONS

CUSTOMER	:	CDE012
SAMPLE CODE	:	SH800480T033-IHC19
MASS PRODUCTION CODE	:	PH800480T033-IHC19
PCAP FIRMWARE VERSION	:	GRE6158A_PL0500_800X480_L21F70V01_COF_20200307.BIN
SAMPLE VERSION	:	01
SPECIFICATIONS EDITION	:	002
DRAWING NO. (Ver.)	:	LMD-PH800480T033-IHC19(Ver.002)
PACKAGING NO. (Ver.)	:	PKG-PH800480T033-IHC19(Ver.001)

Customer Approved

Date:

Approved	Checked	Designer
廖志豪 Rex Liao	張慶源 Yuan Chang	陳宗淇 Howard Chen

POWERTIP
2020.05.12
TW RD APR

☐ Preliminary specification for design input

■ Specification for sample approval

POWERTIP TECH. CORP.

Headquarters: No.8, 6th Road, Taichung Industrial Park, Taichung, Taiwan
台中市 407 工業區六路 8 號

TEL: 886-4-2355-8168
FAX: 886-4-2355-8166

E-mail: sales@powertip.com.tw
Http://www.powertip.com.tw

History of Version

Date (mm / dd / yyyy)	Ver.	Edi.	Description	Page	Design by
03/25/2020	**01**	**001**	**New Drawing.**	**-**	**Howard**
05/11/2020	**01**	**002**	**New Sample.** **Modify Modify FPC suggested connector**	**-** **Appendix**	**Howard**

Contents

1. SPECIFICATIONS
   - 1.1 Features
   - 1.2 Mechanical Specifications
   - 1.3 Absolute Maximum Ratings
   - 1.4 DC Electrical Characteristics
   - 1.5 Optical Characteristics
   - 1.6 Backlight Characteristics
   - 1.7 Touch Panel Specification
2. MODULE STRUCTURE
   - 2.1 Counter Drawing
   - 2.2 Interface Pin Description
   - 2.3 Timing Characteristics
3. QUALITY ASSURANCE SYSTEM
   - 3.1 Quality Assurance Flow Chart
   - 3.2 Inspection Specification
4. RELIABILITY TEST
   - 4.1 Reliability Test Condition
5. PRECAUTION RELATING PRODUCT HANDLING
   - 5.1 Safety
   - 5.2 Handling
   - 5.3 Storage
   - 5.4 Terms of Warranty

Appendix：1.LCM Drawing
2. Packing Specification

Note : For detailed information please refer to IC data sheet :
Primacy(TFT LCD):
ILITEK: ILI6122 / ILI5960

1. SPECIFICATIONS

1.1 Features

Item	Standard Value
Display Resolution	800 * 3 (RGB) * 480 Dots
LCD Type	a-Si TFT , Normally white, Transmissive type
Touch Panel	True Multi-Touch Capacitive Touch Panel True Multi-touch with up to 5 Points of Absolution
Screen size(inch)	5.0 inch
Viewing Direction	6 O'clock
Surface treatment	Anti-Glare
Color configuration	RGB Vertical Strip
Backlight Type	White LED B/L
Weight	85 g
Interface	24 Bits RGB interface
ROHS	THIS PRODUCT CONFORMS THE ROHS OF PTC Detail information please refer website : http://www.powertip.com.tw/news_detail.php?Key=1&cID=1

1.2 Mechanical Specifications

Item	Standard Value	Unit
Outline Dimension	131.0(W) x 90.5 (L) x 5.0(H)	mm

LCD panel

Item	Standard Value	Unit
Viewing Area	109.0(L) * 65.8 (W)	mm
Active Area	108.0 (W) * 64.8 (L)	mm

Note : For detailed information please refer to LCM drawing

1.3 Absolute Maximum Ratings

Module

Item	Symbol	Condition	Min.	Max.	Unit	Remark
Power Supply for TFT Panel	VDD	GND=0	-0.3	4.5	V	-
Power Supply for Backlight Unit	VCC	GND=0	-0.3	+20.0	V	
Operating Temperature	T_{OP} (Ts)	Note 1	-20	70	°C	
Storage Temperature	T_{ST} (Ta)	Note 2	-30	80	°C	

The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Note 1：Ts is the temperature of panel's surface.

Note 2：Ta is the ambient temperature of samples.

1.4 DC Electrical Characteristics

Module GND = 0V, Ta = 25°C

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Power Supply for TFT Panel	VDD	GND=0V	3.0	3.3	3.6	V
Power Supply for Backlight Unit	VCC	GND=0V	5	12	15	V
Input Voltage for TFT Panel	V_{IH}	GND=0V	0.7VDD	-	VDD	V
	V_{IL}	GND=0V	0	-	0.3VDD	
Supply Current for TFT Panel	IDD	IDD@VDD=3.3V	-	100	150	mA
Supply Current for Backlight Unit	ICC	ICC@VCC=5V	-	400	600	
Supply Current for Backlight Unit	ICC	ICC@VCC=12V	-	150	250	
Input Voltage for PWM Signal	VPH	GND=0V	1.2	-	-	V
	VPL	GND=0V	-	-	0.4	V
Dimming Clock Rate	fP	GND=0V	5	-	100	KHz

1.5 Optical Characteristics

TFT LCD Module VDD= 3.3 V, Ta=25°C

Item		Symbol	Condition	Min.	Typ.	Max.	unit	-
Response time	Tr+Tf	25℃	-	-	24	36	ms	-
Viewing angle	Top	θY+	CR ≥ 10		60	-	Deg.	Note 4
	Bottom	θY-			60	-		
	Left	θX-			60	-		
	Right	θX+			60	-		
Contrast ratio		CR	Ta = 25°C θX , θY = 0°	500	600	-	-	Note 3
Color of CIE Coordinate （With B/L & T/P）	White	X		0.24	0.29	0.34	-	Note1
		Y		0.27	0.32	0.37		
	Red	X		0.51	0.56	0.61		
		Y		0.28	0.33	0.38		
	Green	X		0.29	0.34	0.39		
		Y		0.54	0.59	0.64		
	Blue	X		0.08	0.13	0.18		
		Y		0.03	0.08	0.13		
Average Brightness Pattern=white display (With T/P)*1		IV	VCC=5V PWM="High" (Duty=100%)	680	850	-	cd/m2	Note1
Uniformity (With T/P)*2		△B	VCC=5V PWM="High" (Duty=100%)	70	-	-	%	Note1

Note 1:

*1：△B=B(min) / B(max) * 100%

*2：Measurement Condition for Optical Characteristics:

a：Environment: 25℃±5℃ / 60±20%R.H，no wind，dark room below 10 Lux at typical lamp current and typical operating frequency.

b：Measurement Distance: 500 ± 50 ㎜ ，(θ= 0°)

c：Equipment: TOPCON BM-7 fast，(field 1°)，after 10 minutes operation.

d：The uncertainty of the C.I.E coordinate measurement ±0.01，Average Brightness ± 4%

Colorimeter=BM-7 fast

To be measured at the center area of panel with a viewing cone of 1° by Topcon luminance meter BM-7, after 10 minutes operation (module)

Note2: Definition of response time:

The output signals of photo detector are measured when the input signals are changed from “black” to “white”(falling time) and from “white” to “black”(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of Amplitudes.

Refer to figure as below:

Normally White

Normally Black

Note3: Definition of contrast ratio:

Contrast ratio is calculated with the following formula

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at “White” state}}{\text{Photo detector output when LCD is at “Black” state}}$$

Note4: Definition of viewing angle:

Refer to figure as below:

1.6 Backlight Characteristics

Maximum Ratings

Item	Symbol	Min.	Max.	Unit	Remark
LED Forward Current	I_F	180		mA	
LED Reverse Voltage	V_R	30		V	

Electrical / Optical Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
LED Voltage	V_L	16.2	18.0	19.2	V	Note1
LED Current	I_L	-	90	-	mA	-
LED life time	-	50,000	-	-	H_r	Note2

Note 1: The LED Supply Voltage is defined by the number of LED at Ta=25℃ and I_L =90 mA.

Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at Ta=25℃ and I_L =90 mA. The LED life time could be decreased if operating I_L is larger than 90 mA.

1.7 Touch Panel Characteristics

Features

Item	Standard Value
Touch Panel Size	5.0”
Touch type	True Multi-Touch Capacitive Touch Panel
Input Method	True Multi-touch with up to 5 Points of Absolution X and Y Coordinates
Output Interface	I^2C
IC	HYCON----HY4635

I^2C Address

Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
0	1	1	1	0	0	0	**R/W**

Bit 0: 0 for Write / 1 for Read

Mechanical Specifications

Item	Standard Value	Unit
Outline Dimension	Refer to drawing	-

Absolute Maximum Ratings

Item	Symbol	Condition	Min.	Max.	Unit
Supply voltage	TPVDD	-	-0.2	4.0	V
Operating Temperature	T_{OP}	Non condenssing	-20	70	°C
Storage Temperature	T_{ST}	Non condenssing	-30	80	°C

DC Electrical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Power Supply Voltage	TPVDD	-	2.8	3.3	3.6	V
Input High Voltage	VIH	-	-	-	0.7 * TPVDD	V
Input Low Voltage	VIL	-	-	-	0.3 * TPVDD	V

Optical Characteristics

Item	Standard Value	Unit
Total light transmittance	85% or more	-
Hardness	⩾7H	-

PCAP Firmware Information

File: GRE6158A_PL0500_800X480_L21F70V01_COF_20200307.BIN

SHA-256: 34DADA0FA84441E55259CA673B6BC852C3C8AC633CA5F4FA5B6BE5D21E871B15

Remark: None

2. MODULE STRUCTURE

2.1 Counter Drawing

2.1.1 LCM Mechanical Diagram

* See Appendix

2.1.2 Block Diagram

2.2 Interface Pin Description

Pin#	Name	DESCRIPTION
1	GND	Power ground.
2	VDD	Power for Digital Circuit.
3	VDD	Power for Digital Circuit.
4	VCC	Power For LED backlight.
5	VCC	Power For LED backlight.
6	PWM	Shutdown & Dimming control input for backlight. Do not allow this pin to float. “Hi” =100%, “Low” = 0%.
7	GND	Power ground.
8	R0	Red Data.
9	R1	Red Data.
10	R2	Red Data.
11	R3	Red Data.
12	GND	Power ground.
13	R4	Red Data.
14	R5	Red Data.
15	R6	Red Data.
16	R7	Red Data.
17	GND	Power ground.
18	G0	Green Data.
19	G1	Green Data.
20	G2	Green Data.
21	G3	Green Data.
22	GND	Power ground.
23	G4	Green Data.
24	G5	Green Data.
25	G6	Green Data.
26	G7	Green Data.
27	GND	Power ground.
28	B0	Blue Data.
29	B1	Blue Data.

Pin#	Name	DESCRIPTION
30	B2	Blue Data.
31	B3	Blue Data.
32	GND	Power ground.
33	B4	Blue Data.
34	B5	Blue Data.
35	B6	Blue Data.
36	B7	Blue Data.
37	GND	Power ground.
38	HS	Line synchronization signal. Horizontal Sync Input.
39	VS	Frame synchronization signal. Vertical Sync Input.
40	GND	Power ground.
41	DE	Display enable pin from controller. Data Input Enable.
42	GND	Power ground.
43	DCLK	Sample clock. Data will be latched at the falling edge of DCLK.
44	GND	Power ground.
45	CS(NC) / ID1	No Function./ ID[4:1]These pins select LCM type. See NOTE1
46	SDIN(NC) / ID2	No Function./ ID[4:1]These pins select LCM type. See NOTE1
47	SCK(NC) / ID3	No Function ./ ID[4:1]These pins select LCM type. See NOTE1
48	DISPLAY CONTROL /	Display Enable(Hi Active)./ ID[4:1]These pins select LCM type. See NOTE1
49	/RESET	Global Reset (Low Active).
50	GND	Power ground.

Note1

ID Pins Definition:

	PIN 45 ID1	PIN 46 ID2	PIN 47 ID3	PIN 48 ID3
3.5” Module	X	0	0	X
4.3” Module	X	1	0	X
5.0” Module	X	0	1	X
7.0” Module	X	1	1	X

1. Resistor=10k ohm
2. “X”=No use .

Capacitive Touch Panel(CTP) Interface

Pin No.	Symbol	Function
1	GND	Touch Panel ground.
2	TPVDD	Power Supply Voltage (3.3V)
3	SCL	I2C Clock
4	SDA	I2C Data
5	INT	The Interrupt the CTP to the Host
6	RESET	RESET

POWERTIP

2.3 Timing Characteristics

2.3.1 Input Clock and Data Timing

Parameters	Symbol	Spec			Unit	Conditions
		Min.	Typ.	Max.		
VDD Power ON slew rate	t_{POR}	--	--	20	ms	0V ~ 0.9VDD
RSTB pulse width	t_{RST}	10	--	--	us	CLKIN=50MHz
CLKIN cycle time	t_{CPH}	20	--	--	ns	
CLKIN pulse duty	t_{CWH}	40	50	60	%	
VSD setup time	t_{VST}	8	--	--	ns	
VSD hold time	t_{VHD}	8	--	--	ns	
HSD setup time	t_{HST}		--	--	ns	
HSD hold time	t_{HHD}	8	--	--	ns	
Data setup time	t_{DST}	8	--	--	ns	D0[7:0], D1[7:0], D2[7:0] to CLKIN
Data hold time	t_{DHD}	8	--	--	ns	D0[7:0], D1[7:0], D2[7:0] to CLKIN
DE setup time	t_{EST}	8	--	--	ns	
DE hold time	t_{EHD}	8	--	--	ns	
Output stable time	t_{SST}	--	--	6	us	10% to 90% target voltage. CL=120pF, R=10KW
CLKIN frequency	f_{CLK}	--	40	50	MHZ	VDD=3.0 ~ 3.6V
CLKIN cycle time	f_{CLK}	20	25	--	ns	
CLKIN pulse duty	t_{CWH}	40	50	60	%	T_{CLK}
Time from HSD to Source output	t_{HSO}	--	20	--	CLKIN	
Time from HSD to LD	t_{HLD}	--	20	--	CLKIN	Note (2)
Time from HSD to STV	t_{HSTV}	--	2	--	CLKIN	
Time from HSD to CKV	t_{HCKV}		20	--	CLKIN	
Time from HSD to OEV	t_{HOEV}	--	4	--	CLKIN	
LD pulse width	t_{WLD}	--	10		CLKIN	Note (2)
CKV pulse width	t_{WCKV}	--	66	--	CLKIN	
OEV pulse width	t_{WOEV}	--	74	--	CLKIN	

Note: (1) VDD=3.0 ~ 3.6V, VDDA=6.5~13.5V, DGND=AGND=0V, Ta=-20~+85℃

(2) The contents of the data register are transferred to the latch circuit at the rising edge of LD. Then the gray scale voltage is output from the device at the falling edge of LD.

2.3.2 Vertical input timing

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Vertical display area	tvd		480		H
VSYNC period time	tv	510	525	650	H
VSYNC pulse width	tvpw	1	-	20	H
VSYNC back Porch(Blanking)	tvb	23	23	23	H
VSYNC Front Porch	tvfb	7	22	147	H

2.3.3Horizontal Input Timing

Parameter		Symbol	Value			Unit
			Min	Typ	Max	
Horizontal display area		thd	800			DCLK
DCLK frequency		fclk	-	33.3	50	MHz
1 Horizontal Line		th	862	1056	1200	DCLK
HSD pulse width	Min	thpw	-	1		
	Typ		-	-		
	Max		-	40		
HSD Back Porch (Blacking)		thp	46	46	46	
HSD Front Proch		thfb	16	210	354	

3. QUALITY ASSURANCE SYSTEM

3.1 Quality Assurance Flow Chart

Item	Customer	Sales	R&D	Q.A	Manufacturing	Product control	Purchase	Inventory control
Sales Service								
Q.A Activity	1. ISO 9001 Maintenance Activities 2. Process improvement proposal 3. Equipment calibration 4. Education And Training Activities 5. Standardization Management							

3.2. Inspection Specification

◆Scope: The document shall be applied to TFT-LCD Module for 3.5" -15" (Ver.B01).

◆Inspection Standard: MIL-STD-105E Table Normal Inspection Single Sampling Level Ⅱ.

◆Equipment: Gauge, MIL-STD, Powertip Tester, Sample

◆Defect Level: Major Defect AQL: 0.4; Minor Defect AQL: 1.5

◆OUT Going Defect Level: Sampling.

◆Standard of the product appearance test:

a. Manner of appearance test:

(1). The test best be under 20W×2 fluorescent light(about 300lux ～500lux)

, and distance of view must be at 30~40 cm.

(2). The test direction is base on about around 45° of vertical line.

(3). Definition of area.

A area: viewing area

B area: Outside of viewing area

(4). Standard of inspection： (Unit：mm)

◆Specification For TFT-LCD Module 3.5” ~15” : (Ver.B01)

<table>
<tr><th>NO</th><th>Item</th><th>Criterion</th><th>Level</th></tr>
<tr><td rowspan="3">01</td><td rowspan="3">Product condition</td><td>1.1The part number is inconsistent with work order of production.</td><td>Major</td></tr>
<tr><td>1.2 Mixed product types.</td><td>Major</td></tr>
<tr><td>1.3 Assembled in inverse direction.</td><td>Major</td></tr>
<tr><td>02</td><td>Quantity</td><td>2.1The quantity is inconsistent with work order of production.</td><td>Major</td></tr>
<tr><td>03</td><td>Outline dimension</td><td>3.1Product dimension and structure must conform to structure diagram.</td><td>Major</td></tr>
<tr><td rowspan="6">04</td><td rowspan="6">Electrical Testing</td><td>4.1 Missing line character and icon.</td><td>Major</td></tr>
<tr><td>4.2 No function or no display.</td><td>Major</td></tr>
<tr><td>4.3 Display malfunction.</td><td>Major</td></tr>
<tr><td>4.4 LCD viewing angle defect.</td><td>Major</td></tr>
<tr><td>4.5 Current consumption exceeds product specifications.</td><td>Major</td></tr>
<tr><td>4.6Mura cannot be seen through 5% ND filter at 50% Gray , should be judged by the viewing angle of 90 degree.</td><td>Minor</td></tr>
<tr><td>05</td><td>Dot defect

(Bright dot, Dark dot)

On -display</td><td>
<table>
<tr><th colspan="2">Item</th><th>Acceptance (Q’ty)</th></tr>
<tr><td rowspan="4">Dot Defect</td><td>Bright Dot</td><td>≦ 4</td></tr>
<tr><td>Dark Dot</td><td>≦ 5</td></tr>
<tr><td>Joint Dot</td><td>≦ 3</td></tr>
<tr><td>Total</td><td>≦ 7</td></tr>
</table>
5.1 Inspection pattern: full white, full black, Red, Green and blue screens.
5.2 It is defined as dot defect if defect area ＞1/2 dot.
5.3 The distance between two dot defect ≧5 mm.
5.4 Bright dot that can not be seen through 5% ND filter.
</td><td>Minor</td></tr>
</table>

◆Specification For TFT-LCD Module 3.5″ ~15″ : (Ver.B01)

<table>
<tr><th>NO</th><th>Item</th><th>Criterion</th><th>Level</th></tr>
<tr><td>06</td><td>Black or white Dot, scratch, contamination

Round type

Φ=(x+y) / 2

Line type

</td><td>6.1 Round type (Non-display or display):
<table><tr><th rowspan="2">Dimension (diameter：Φ)</th><th colspan="2">Acceptance (Q’ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>Φ ≦ 0.25</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>0.25 ＜ Φ ≦ 0.50</td><td>5</td></tr><tr><td>Φ ＞ 0.50</td><td>0</td></tr><tr><td>Total</td><td>5</td></tr></table>
6.2 Line type(Non-display or display):
<table><tr><th rowspan="2">module size</th><th rowspan="2">Length (L)</th><th rowspan="2">Width (W)</th><th colspan="2">Acceptance (Q’ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td rowspan="5">3.5” to less 9”</td><td>---</td><td>W ≦ 0.03</td><td>Ignore</td><td rowspan="5">Ignore</td></tr><tr><td>L ≦10.0</td><td>0.03 ＜W ≦ 0.05</td><td>4</td></tr><tr><td>L ≦5.0</td><td>0.05 ＜W ≦ 0.10</td><td>2</td></tr><tr><td>---</td><td>W ＞0.10</td><td>As round type</td></tr><tr><td colspan="2">Total</td><td>5</td></tr><tr><td rowspan="4">9” to 15”</td><td>---</td><td>W ≦ 0.05</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>L ≦10.0</td><td>0.05 ＜W ≦ 0.10</td><td>5</td></tr><tr><td>---</td><td>W ＞0.10</td><td>As round type</td></tr><tr><td colspan="2">Total</td><td>5</td></tr></table></td><td>Minor</td></tr>
<tr><td>07</td><td>Polarizer Bubble</td><td><table><tr><th rowspan="2">Dimension (diameter: Φ)</th><th colspan="2">Acceptance (Q’ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>Φ ≦ 0.25</td><td>Ignore</td><td rowspan="5">Ignore</td></tr><tr><td>0.25 ＜ Φ ≦ 0.50</td><td>4</td></tr><tr><td>0.50 ＜ Φ ≦ 0.80</td><td>1</td></tr><tr><td>Φ ＞0.80</td><td>0</td></tr><tr><td>Total</td><td>5</td></tr></table></td><td>Minor</td></tr>
</table>

◆Specification For TFT-LCD Module 3.5″ ~15″：

(Ver.B01)

NO	Item	Criterion	Level
08	The crack of glass	**Symbols：** X: The length of crack　　Y: The width of crack. Z: The thickness of crack　　W: terminal length t: The thickness of glass　　a: LCD side length --- 8.1 General glass chip: 8.1.1 Chip on panel surface and crack between panels: X: ≦ a; Y: Crack can't enter viewing area; Z: ≦1/2 t X: ≦ a; Y: Crack can't exceed the half of SP width.; Z: 1/2 t < Z ≦2 t	Minor

◆Specification For TFT-LCD Module 3.5″ ~15″：

(Ver.B01)

NO	Item	Criterion	Level
08	The crack of glass	Symbols： X: The length of crack　Y: The width of crack. Z: The thickness of crack　W: terminal length t: The thickness of glass　a: LCD side length 8.1.2 Corner crack: X: ≦1/5 a; Y: Crack can't enter viewing area; Z: Z ≦ 1/2 t X: ≦1/5 a; Y: Crack can't exceed the half of SP width.; Z: 1/2 t < Z ≦ 2 t	Minor
		8.2 Protrusion over terminal: 8.2.1 Chip on electrode pad: Front: X ≦ a; Y ≦ 1/2 W; Z ≦ t Back: X ≦ a; Y ≦ W; Z ≦ 1/2 t	

◆Specification For TFT-LCD Module 3.5″ ~15″ : (Ver.B01)

<table>
<tr><th>NO</th><th>Item</th><th>Criterion</th><th>Level</th></tr>
<tr><td>08</td><td>The crack of glass</td><td>
Symbols:
X: The length of crack Y: The width of crack.
Z: The thickness of crack W: terminal length
t: The thickness of glass a: LCD side length
8.2.2 Non-conductive portion:

<table>
<tr><th>X</th><th>Y</th><th>Z</th></tr>
<tr><td>≦ 1/3 a</td><td>≦ W</td><td>≦t</td></tr>
</table>
⊙ If the chipped area touches the ITO terminal, over 2/3 of
1. the ITO must remain and be inspected according to electrode terminal specifications.
8.2.3 Glass remain:

<table>
<tr><th>X</th><th>Y</th><th>Z</th></tr>
<tr><td>≦ a</td><td>≦ 1/3 W</td><td>≦t</td></tr>
</table>
8.2.4 Cracking:

Not Allowed
</td><td>Minor</td></tr>
</table>

◆Specification For TFT-LCD Module 3.5″ ~15″：

(Ver.B01)

NO	Item	Criterion	Level
09	Backlight elements	9.1 Backlight can't work normally.	Major
		9.2 Backlight doesn't light or color is wrong.	Major
		9.3 Illumination source flickers when lit.	Major
10	General appearance	10.1Pin type、quantity、dimension must match type in structure diagram.	Major
		10.2 No short circuits in components on PCB or FPC.	Major
		10.3 Parts on PCB or FPC must be: no wrong parts, missing parts or excess parts.	Major
		10.4 Product packaging must the same as specified on packaging specification sheet.	Minor
		10.5 The folding and peeled off in polarizer are not acceptable.	Minor
		10.6 The PCB or FPC between B/L assembled distance(PCB or FPC) is ≦1.5 mm.	Minor

4. RELIABILITY TEST

4.1 Reliability Test Condition (Ver.B01)

NO.	TEST ITEM	TEST CONDITION
1	High Temperature Storage Test	Keep in +80 ±2℃ 240 hrs
2	Low Temperature Storage Test	Keep in -30 ±2℃ 240 hrs
3	High Temperature / High Humidity Storage Test	Keep in +60℃ / 90% R.H duration for 240 hrs
4	Temperature Cycling Storage Test	-30℃ → +25℃ → +80℃ → +25℃ (30mins) (5mins) (30mins) (5mins) 10 Cycle
5	ESD Test	Air Discharge: Apply 2 KV with 5 times Discharge for each polarity +/- Contact Discharge: Apply 250 V with 5 times discharge for each polarity +/- 1. Temperature ambiance : 15℃～35℃ 2. Humidity relative : 30%～60% 3. Energy Storage Capacitance(Cs+Cd) : 150pF±10% 4. Discharge Resistance(Rd) : 330Ω±10% 5. Discharge, mode of operation : Single Discharge (time between successive discharges at least 1 sec) (Tolerance if the output voltage indication : ±5%)
6	Vibration Test (Packaged)	1. Sine wave 10～55 Hz frequency (1 min/sweep) 2. The amplitude of vibration :1.5 mm 3. Each direction (X、Y、Z) duration for 2 Hrs
7	Drop Test (Packaged)	Packing Weight (Kg) / Drop Height (cm) 0 ~ 45.4 / 122 45.4 ~ 90.8 / 76 90.8 ~ 454 / 61 Over 454 / 46 Drop Direction :※1 corner / 3 edges / 6 sides each 1time

◎Result Evaluation Criteria :

Under the display quality test conditions with normal operations with normal operation state. Do not change these conditions as such changes may affect practical display function.

(Normal operation state)

Temperature：+20~30℃

Humidity：50~70%

Atmospheric pressure：86~106Kpa

5. PRECAUTION RELATING PRODUCT HANDLING

5.1 SAFETY

5.1.1 If the LCD panel breaks , be careful not to get the liquid crystal to touch your skin.

5.1.2 If the liquid crystal touches your skin or clothes , please wash it off immediately by using soap and water.

5.2 HANDLING

5.2.1 Avoid any strong mechanical shock which can break the glass.

5.2.2 Avoid static electricity which can damage the CMOS LSI—When working with the module , be sure to ground your body and any electrical equipment you may be using.

5.2.3 Do not remove the panel or frame from the module.

5.2.4 The polarizing plate of the display is very fragile. So , please handle it very carefully, do not touch , push or rub the exposed polarizing with anything harder than an HB pencil lead (glass , tweezers , etc.)

5.2.5 Do not wipe the polarizing plate with a dry cloth , as it may easily scratch the surface of plate.

5.2.6 Do not touch the display area with bare hands , this will stain the display area.

5.2.7 Do not use ketonics solvent & aromatic solvent. Use with a soft cloth soaked with a cleaning naphtha solvent.

5.2.8 To control temperature and time of soldering is 320 ± 10°C and 3-5 sec.

5.2.9 To avoid liquid (include organic solvent) stained on LCM

5.2.10 Caution! (LCM products with Capacitive Touch Panel)

Strong EMI-sources such as switch-mode power supplies (SMPS) can lead to touch malfunction (e.g. ghost-touches).

Therefore, the touch needs to be thoroughly tested inside the target application.

5.2.11 Caution: Continuously displaying same static image will result in high possibility of image sticking/image burn-in effect due to TFT panel characteristic.

5.3 STORAGE

5.3.1 Store the panel or module in a dark place where the temperature is 25°C ± 5°C and the humidity is below 65% RH.

5.3.2 Do not place the module near organics solvents or corrosive gases.

5.3.3 Do not crush , shake , or jolt the module.

5.4 TERMS OF WARRANTY

5.4.1 Applicable warrant period

The period is within thirteen months since the date of shipping out under normal using and storage conditions.

5.4.2 Unaccepted responsibility

This product has been manufactured to your company's specification as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment, we cannot take responsibility if the product is used in nuclear power control equipment, aerospace equipment , fire and security systems or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required.

NOTES:
1.LCD TYPE:TFT
2.LCD DISPLAY: POSITIVE/TRANSMISSIVE
3.VIEW DIRECTION: 6 O'CLOCK
4.The tolerance unless classified ±0.3mm
5. Component & Unbending area. Kapton tape EMI Film
6.A: PITCH 0.5X49=24.5±0.1;W=0.35±0.1
7.B: PITCH 0.5X5=2.5±0.1;W=0.35±0.1
8.LCM FPC suggested connector : FH12A-50S-0.5SH (Hirose) or Compatible
9.T/P FPC suggested connector : FH34SRJ-6S-0.5SH(50) (Hirose) or Compatible

REV	REV BY	REVISER	DATE
007			
006			
005			
004			
003			
002	Modfiy FPC suggested connector	Kevin Lin	2020/05/11
001	NEW DRAWING	Kevin Lin	2020/03/25

PART NO: PH800480T033-IHC19

DRAWING NAME : LMD-PH800480T033-IHC19

TITLE: LCD MODULE DRAWING

久正光電股份有限公司
POWERTIP TECHNOLOGY CORPORATION

Design	Kevin Lin	(3)	Surface		
Check	Clare	Unit	MM	Material	
Approve	Rex	Scale	FIT	Thickness	
		Page	1/1	Quantity	

Length(Min) (mm) \ Tolerance Precision	Precision Level
1 ~ 4	-
4 ~ 16	-
16 ~ 63	-
63 ~ 250	-
250 ~ 1000	-

PT-A-054-01

Ver.001	
Documents NO.	PKG-PH800480T033-IHC19

LCM包裝規格書
LCM Packaging Specifications
(For Tray)

Approve	Check	Contact
Rex	Clare	Kevin Lin

1.包裝材料規格表 (Packaging Material) : (per carton)

No.	Item	Model	Dimensions (mm)	1Pcs Weight	Quantity	Total Weight
1	成品 (LCM)	PH800480T033-IHC19	131.0 X 90.5	0.093	144	13.392
2	多層薄膜(1)POF	OTFILM0BA03ABA	19"X350X0.015	——	6	——
3	TRAY 盤 (2)Tray	TYSG000000187	352 X 260 X 12.8	0.0965	42	4.053
4	舒美墊(3) EPE	FOAM000000047	350 X 255 X 5	0.011	6	0.066
5	內盒(4)Product Box	BX36627063ABBA	383 X 270 X 66	0.182	6	1.092
6	保利龍板(5)Polylon board	OTPLB00PL08ABA	550 X 393 X 20	0.0284	2	0.0568
7	外紙箱(6)Carton	BX57041027CCBA	570 X 410 X 265	1.0	1	1.0
8						
9						

2.一 整箱總重量 (Total LCD Weight in carton) : 19.66 Kg±10%

3.單箱數量規格表 (Packaging Specifications and Quantity) :

(1)LCM quantity per box : no per tray	4	x no of tray	6	=	24
(2)Total LCM quantity in carton : quantity per box	24	x no of boxes	6	=	144

特 記 事 項 (REMARK)

4.TRAY盤相疊時,需旋轉180度,請詳見B視圖
Rotate tray 180 degrees and place on top of stack.
Check the tray stack using Fig. B.

5.外購Tray:TY00000000308
自製Tray:TYSG000000187

POWERTIP TECH. CORP.